

Tubing Specification:

Size		Grade&End Type							Standard
OD /mm (in)	WT /mm	H40	J55	L80-1, L80-13Cr, R95	N80-1, N80Q	C90	T95	P110	
42.16 (1.660")	3.18								API SPEC 5CT
	3.56	N/U	N/U	N/U	N/U	N/U	N/U		
	4.85	U	U	U	U	U	U	U	
48.26 (1.900")	3.18	N/U	N/U	N/U	N/U	N/U	N/U		
	3.68	N/U	N/U	N/U	N/U	N/U	N/U		
	5.08	U	U	U	U	U	U	U	
	6.35								
	7.62								
60.32 (2-3/8")	4.24								
	4.83								
	6.45								
	7.49								
	8.53								
73.02 (2-7/8")	5.51	N/U	N/U	N/U	N/U	N/U	N/U	N/U	
	7.01			N/U	N/U	N/U	N/U	N/U	
	7.82			N/U	N/U	N/U	N/U	N/U	
	8.64				U			U	
	9.96								
	11.18	U	N	N	N	N	N	N	
88.9 (3-1/2")	5.49								
	6.45	N/U	N/U	N/U	N/U	N/U	N/U	N/U	
	7.34	N	N	N	N	N	N		
	9.52			N/U	N/U	N/U	N/U	N/U	
	10.92								
	12.09								



	13.46								
101.6 (4")	5.74	N	N	N	N	N	N	N	N
	6.65	U	U	U	U	U	U	U	U
	8.38								
	10.54								
	12.7								
	15.49								
114.3 (4-1/2")	6.88	N/U	N/U	N/U	N/U	N/U	N/U	N/U	N/U
	8.56								
	9.65								
	10.92								
	12.7								
	14.22								
	16								

Casing Specification

Size		Grade&End Type									Standard
OD /mm	WT /mm	H40	J55, K55	M65	L80-1, L80-13C r, R95	N80-1, N80Q	C90, T95	C110	P110	Q125	
114.3 (4-1/2")	5.21	S	S	S							API SPEC 5CT
	5.69		S/B	S/B							
	6.35		S/L/B	L/B	L/B	L/B	L/B		L/B		
	7.37			L/B	L/B	L/B	L/B		L/B		
	8.56								L/B	L/B	
127 (5")	5.59		S	S							
	6.43		S/L/B	S/L/B							
	7.52		S/L/B	L/B	S/L/B	S/L/B	L/B		S/L/B		
	9.19			L/B	S/L/B	S/L/B	L/B		S/L/B	L/B	



WU STEEL

Serving The Industrial World

	11.1			L/B	L/B	L/B	L/B		L/B	L/B	
	12.14				L/B	L/B	L/B		L/B	L/B	
	12.7				L/B	L/B	L/B		L/B	L/B	
139.7 (5-1/2")	6.2	S	S	S							
	6.98		S/L/B	S/L/B							
	7.72		S/L/B	L/B	S/L/B	S/L/B	L/B		S/L/B		
	9.17			L/B	S/L/B	S/L/B	L/B		S/L/B		
	10.54			L/B	S/L/B	S/L/B	L/B		S/L/B	S/L/B	
168.28 (6-5/8")	7.32			S/L/B							
	8.94			L/B					S/L/B		
	10.59			L/B					S/L/B		
	12.06								S/L/B	L/B	
177.8 (7")	6.91	S	S	S							
	8.05		S/L/B	L/B	S/L/B	S/L/B	L/B				
	9.19			L/B	S/L/B	S/L/B	L/B		S/L/B		
	10.36			L/B	S/L/B	S/L/B	L/B		S/L/B		
	11.51			L/B	S/L/B	S/L/B	L/B		S/L/B		
	12.65				S/L/B	S/L/B	L/B		S/L/B	S/L/B	
	13.72				S/L/B	S/L/B	L/B		S/L/B	S/L/B	
193.68 (7-5/8")	8.33		S/L/B	S/L/B	L/B	L/B	L/B				
	9.52			L/B	L/B	L/B	L/B		L/B		
	10.92			L/B	L/B	L/B	L/B		L/B		
	12.7				L/B	L/B	L/B		L/B	L/B	
	14.27				L/B	L/B	L/B		L/B	L/B	
	15.11				L/B	L/B	L/B		L/B	L/B	
	15.88				L/B	L/B	L/B		L/B	L/B	
219.08 (8-5/8")	6.71		S	S	S						API
	7.72	S	S/L/B	S							SPE
	8.94	S	S/L/B	S/L/B							C
											5CT



	10.16			S/L/B	L/B	L/B	L/B		L/B	
	11.43			L/B	L/B	L/B	L/B		L/B	
	12.7				L/B	L/B	L/B		L/B	
	14.15				L/B	L/B	L/B		L/B	L/B
244.48 (9-5/8")	8.94	S	S/L/B	S/L/B						
	10.03		S/L/B	S/L/B	L/B	L/B	L/B		L/B	
	11.05			L/B	L/B	L/B	L/B		L/B	
	11.99			L/B	L/B	L/B	L/B		L/B	L/B
	13.84				L/B	L/B	L/B		L/B	L/B
	15.11	S			L/B	L/B	L/B		L/B	
273.05 (10-3/8")	8.89	S/B		S/B						
	10.16	S/B	S/B	S/B						
	11.43	S/B	S/B	S/B	S/B	S/B	S/B		S/B	
	12.57				S/B	S/B	S/B		S/B	
	13.84						S/B		S/B	S/B
	15.11						S/B		S/B	S/B
298.45 (11-3/4")	9.65									
	10.92									
	12.19				S/B				S/B	
	13.06				S/B				S/B	S/B
339.72 (13-3/8")	8.38	S								
	9.65		S/B	S/B						
	10.92		S/B	S/B						
	12.19			S/B	S/B	S/B	S/B		S/B	
	13.06				S/B	S/B	S/B		S/B	S/B
406.4 (16")	16.66									
508	16.13		S/L/B							



WUSTEEL

Serving The Industrial World

(20")											
Remark : S-Short long thread ; L-Long round thread ; B-BTC											