

Steel Plate&Coil

Product	Type	Standard	Material	Product Size (WT×Width×L, mm)
Pipeline Steel	Pipeline	API 5L	X42-X80, X70(HIC、SSCC),X100	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		GB/T9711	L245-L555	
Vessel Steel	High quality	ABS/DNV/LR/BV.etc	A、B、D、E	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
	High strength		AH32-AH40、DH32-DH69、EH32-EH69、FH32-FH69	
Structure	Carbon	JISG3101	SS400、SS490、SS540	6~300×900~4100 ×3000~25000 (2-25mm WT for coil)
		GB/T700	Q235、Q275	
		GB711	10-55、20Mn-65Mn	
	Low Alloy	GB/T1591	Q345、Q390、Q420、Q460	
		ASTM	A36、A283、A529	
		EN10025	S235-460J0/JR/J2/M/N(L)	
		JISG3106	SM400、SM490、SM520、SM570	
		EN10113	S275-460M/N(L)	
	Building	GB/T19879	Q345GJ、Q390GJ、Q420GJ、Q460GJ	
		JISG3136	SN400、SN490	
		ASTM	A572、A573、A633	
	Bridge	GB/T714	Q345q、Q370q、Q420q	
		JISG3106	SM490、SM520、SM570	
ASTM		A572、A709Grade5050W100100W		

	High Strength	GB/T16270	Q500、Q550、Q620、Q690	
		JISG3128	SHY685、SHY685N、 SYH685NS	
		ASTM	A514、A710	
		EN10137	S460Q(L)、 S500Q(L)-S960Q(L)	
Pressure	For Boiler	GB713	Q345R、Q370R、15CrMoR 13MnNiMoR、12Cr1MoVR	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		JISG3115	SPV315、SPV355、SPV410	
		ASTM	A202、A204、A515、A516、 A387、A662	
		JIS3103	SB410、SB450、SB480	
		EN10028	P235GH、P265GH、P355GH	
Special	High strength pressure	GB19189	07MnCrMoVR、12MnNiVR	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		JISG3115	SPV450、SPV490	
		ASTM	A517、A537、A542、A543、 A736	
	Low-temperature	GB3531	15MnNiDR、09MnNiDR	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		ASTM	A203、A553	
		GB150	06Ni9DR	
		JISG3127	SL2N、SL3N、SL5N、SL9N	
	Offshore	GB/T712	Z15、Z25、Z35	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		API2W/2H/2Y	Grade50T、 Grade60/Grade42、Grade50	
		ABS	AQ43、DQ43、EQ43、AQ47、 DQ47、EQ47、AQ51、DQ51、 EQ51、AQ56、DQ56、EQ56、 AQ63、DQ63、EQ63、AQ70、 DQ70、EQ70	

		DNV(TMCP)	A40、D40、E40、F36、F40	
Weather resisting		ASTM	A242、A588、A871	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		JISG3125	SPA-H	
		JISG3114	SMA400、SMA490、SMA570	
		GB/T4171	Q295GNH、Q355GNH、 Q235NH-Q550NH	
		EN10025	S355J0WP、S355J2WP	
	Mold& Wear-resisting		JISG4051	
		ASTM	A681-P20	
		GB/T4171	NM360-550	
		QB	XCHT1100	
		QB	XCHD360-450	
Energy		QB	20HR、16MnHR	6~350×910~4100 ×6000~25000 (2-25mm WT for coil)
		ASTM	SA285、SA299、SA533、 SA738、SA841	
		EN10028-3	P275-P460N/NH/NL1/NL2	
		EN10028-5	P355-P460M/ML1/ML2	
		EN10028-6	P355-P690Q/QH/QL1/QL2	